

Product data sheet

Product	Robust™ Membranbånd
Description	<p>Both side fleece coated rubber elastic sealing tape with good lateral Extension. Both side with Polyester fleece coated rubber elastic sealing tape with low textile content. The tape exhibits excellent recovery characteristics and is fully silicone-compatible.</p> <ul style="list-style-type: none">• Easy to use• Elastic• ETAG 022 approved• To be used with Robust Våtromsmembran
Preparation	<p>All loose material, soft or crumbling plaster, dirt and poorly bonded layers of paint must be removed. Absorbent surfaces should be primed with Robust™ Primer - Sugende.</p>
Application	<p>For use in corners and to cover joints. A resistance data table is available. Cut the sealing tape to the required length and press onto the fresh Robust Våtromsmembran, which serves as the adhesive base. Ensure that there is a tape overlap of at least 5 cm. Use a smoothing trowel to level out any uneven areas or distortions. Apply two or three coats and ensure that the tape is fully covered with the sealing compound. When calculating consumption, allow for a tape overlap of at least 5 cm.</p>
Further processing	<p>The tape ensures excellent compatibility and good adhesion with polymer dispersions, flexible mineral sealing compounds and thermosetting resins. However, it is advisable to conduct a compatibility test before applying other products.</p>
Finishing	<p>Tools and soiled areas should be cleaned immediately after use with water.</p>
Storage	<p>Robust Membranbånd can be used for a period of at least 24 months when stored in a cool and dry period.</p>
Technical data	<p>Measurements: 10 and 50m roll.</p> <hr/> <p>Thickness: 0.6 mm.</p> <hr/> <p>Width: 12mm</p> <hr/> <p>Weight: 50g/m</p> <hr/> <p>alent air layer thickness sd: 5m</p> <hr/> <p>Water pressure resistance: Leakproof at 3 bar</p>

Elongation, lateral direction: 250%

Elongation, lengthwise direction: 50%

Temperature resistance: -20°C to +90°C.

Colour: Grey or Blue.

Safety

The product is not hazardous as defined in the hazardous substances code. May be disposed of as building site waste. For health, safety and environment information please read the safety data sheet at www.robustnorge.no.

Packaging

10 and 50m roll per carton.

GTIN

GTIN: 10 m: 7090040902382.

GTIN: 50m: 7090040902405.

Item no

10m: Item no: 238

50m: Item no: 240

Nobb

Warning

All details in this technical information are based on our current knowledge and experience. They are non-binding and do not release the buyer from the duty to undertake their own tests for suitability for the intended application and purpose. A guarantee for the general validity of all details is ruled out with regard to the different processing and construction site conditions. The general rules for construction engineering as well as the valid standards and guidelines must be observed. The publication of this technical information replaces all previous editions. Changes in the scope of product and application engineering further development are reserved. Please obtain the latest information from our internet sites, www.robustnorge.no.

Date of issue

01.06.2016

Company

Steinhardt™ AS

Org. no. 915496059 mva

contact@steinhardt.no

www.steinhardt.no
