

**Robust™ Flislim - Hvit**

Batch number see side sack print

## Declaration of performance

*Labelling of declaration of performance and clear identification code of the product type*

**110336-01-EN12004-C2-TE-S1**

*Intended use*

Highly flexible thin-bed adhesive with extremely high adhesive strength. For light and natural stone that is not susceptible to discoloration. For walls and floors, indoors and outdoors.

*Manufacturer*

**Steinhardt AS • Postboks 8627 Ranheim • 7452 Trondheim, Norway**

*System for assessment and verification of constancy of performance*

**System 4 in case of reaction to fire and System 3 for the other essential characteristics**

*Notified testing body*

**Materialprüfungsamt Nordrhein-Westfalen e.V. (MPA NRW) – Kennnummer 0432**

has carried out the initial test of the product with regard to the essential characteristics (except reaction to fire) of system 3 and issued the following:

*Harmonised standard*

**EN 12004 :2012**

*Declared performance*

Essential characteristics	Performance
Reaction to fire	E
Bond strength	Tensile adhesion strength after dry storage $\geq 1,00$ N/mm <sup>2</sup>
Durability against exposure to climate/heat storage	Tensile adhesion strength after warm storage $\geq 1,00$ N/mm <sup>2</sup>
Durability against exposure to climate/heat storage	Tensile adhesion strength after water storage $\geq 1,00$ N/mm <sup>2</sup>
Durability against exposure to freeze/thaw storage	Tensile adhesion strength after freeze/thaw storage $\geq 1,00$ N/mm <sup>2</sup>
Release of dangerous substances	NPD

The performance of the product conforms with the declared performance. The manufacturer is solely responsible for compiling this declaration of performance which is consistent with the regulation (EU) No. 305/2011.

Signed for the manufacturer and on behalf of the manufacturer of:



*Stian Schevig. Daglig leder, Steinhardt AS.*

Date of issue. 01.06.2016.