

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.08.2016

Revision: 08.08.2016

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name: Robust™ Epoxy - Primer & Lim, Komp. B**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture**  
Solvent-free, transparent, 2-component plastic filler as a top coat, adhesion bridge and for making artificial resin mortar
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Steinhardt AS  
Postboks 8627 Ranheim  
7052 Trondheim  
Norway
- **Further information obtainable from:**  
Steinhardt AS  
Postboks 8627 Ranheim  
7052 Trondheim  
Norway  
+47 72607060. [www.robustnorge.no](http://www.robustnorge.no)
- **1.4 Emergency telephone number:**  
(+47) 22591300  
<https://helsenorge.no/Giftinformasjon>

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS05



GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**  
Carbomonozyklische, alkylierte Gemische aus Poly-aza-Alkanen, hydriert
- **Hazard statements**  
H314 Causes severe skin burns and eye damage.

(Contd. on page 2)

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.08.2016

Revision: 08.08.2016

**Trade name: Robust™ Epoxy - Primer & Lim, Komp. B**

(Contd. of page 1)

H317 May cause an allergic skin reaction.

· **Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P103 Read label before use.  
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P262 Do not get in eyes, on skin, or on clothing.  
 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.  
 · **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**

· **Description:** Amine-containing curing agents for epoxy resins.

· **Dangerous components:**

CAS: 100-51-6 EINECS: 202-859-9	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	25-50%
CAS: 2855-13-2 EINECS: 220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	25-50%
CAS: 1477-55-0 EINECS: 216-032-5	m-phenylenebis(methylamine) ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	10-25%

· **Additional information:**

For the wording of the listed hazard phrases refer to section 16.

GISCODE: RE 1 (Komp. A + B)

### SECTION 4: First aid measures

· **4.1 Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation mindestens 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Call for a doctor immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.08.2016

Revision: 08.08.2016

Trade name: Robust™ Epoxy - Primer &amp; Lim, Komp. B

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**  
NOTE TO PHYSICIANS: Application of Kortikoidcreme has proven to be effective in the treatment of skin irritation.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Foam (alcohol resistant), carbon dioxide, dry chemical, dry sand, limestone powder.
- **5.2 Special hazards arising from the substance or mixture**  
Incomplete combustion carbon monoxide may arise. May evolve ammonia gas. May evolve toxic nitrogen oxides. Burning produces obnoxious and toxic fumes. personnel in wind direction has to be evacuated.
- **5.3 Advice for firefighters**
- **Protective equipment:**  
Avoid contact with skin. Face protection. Use personal protective equipment. In case of fire, if necessary, wear self-contained breathing apparatus.
- **Additional information**  
Water run-off not allow to enter drains or water courses of fire fighting.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Store in a cool, dry place.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in original container.
- **Information about storage in one common storage facility:**  
Do not store together with acids.  
Store away from foodstuffs, beverages and feed.
- **Further information about storage conditions:** Protect from frost.
- **Storage class:** VCI: 8
- **7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.08.2016

Revision: 08.08.2016

Trade name: Robust™ Epoxy - Primer &amp; Lim, Komp. B

(Contd. of page 3)

### SECTION 8: Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**100-51-6 Benzyl alcohol (25-50%)**

WEL | see section IIb

**2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine (25-50%)**

WEL | see section IIb

**1477-55-0 m-phenylenebis(methylamine) (10-25%)**

WEL | see section IV

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

If good ventilation is not required. In inadequately ventilated places and during spray processing, wear respiratory protection. A/P2 filter

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Protective gloves made of nitrile with a layer thickness of at least 0.4 mm reagen (Durchdringungszeit > 480 min see also www.gisbau.de).

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Tightly sealed goggles

· **Body protection:** Impervious clothing.

### SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: liquid

Colour: yellowish

· **Odour:** by amine.

· **Change in condition**

Melting point/Melting range: Undetermined.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.08.2016

Revision: 08.08.2016

Trade name: Robust™ Epoxy - Primer &amp; Lim, Komp. B

(Contd. of page 4)

<b>Boiling point/Boiling range:</b>	205 °C
· <b>Flash point:</b>	101 °C
· <b>Ignition temperature:</b>	435 °C
· <b>Self-igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product does not present an explosion hazard.
· <b>Vapour pressure at 50 °C:</b>	5 hPa
· <b>Density:</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Viscosity:</b>	
<b>Dynamic at 20 °C:</b>	280 mPas
<b>Kinematic:</b>	Not determined.
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**  
Prior to strongly acidic and alkaline materials as well as oxidants in order to avoid exothermic reactions.
- **10.6 Hazardous decomposition products:** Possible at > 60 °C elimination of acrylonitrile.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

#### 100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
------	------	------------------

Dermal	LD50	2000 mg/kg (rbt)
--------	------	------------------

#### 2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral	LD50	1030 mg/kg (rat)
------	------	------------------

#### 1477-55-0 m-phenylenebis(methylamine)

Oral	LD50	1040 mg/kg (rat)
------	------	------------------

Dermal	LD50	2000 mg/kg (rab)
--------	------	------------------

Inhalative	LC50/4 h	2.4 mg/l (rat)
------------	----------	----------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes severe skin burns and eye damage.
- **Serious eye damage/irritation**  
Causes serious eye damage.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.08.2016

Revision: 08.08.2016

Trade name: **Robust™ Epoxy - Primer & Lim, Komp. B**

(Contd. of page 5)

- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.


### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Must not reach sewage water or drainage ditch undiluted or unneutralised.  
Harmful to aquatic organisms  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
  - **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
  - **European waste catalogue**
- |           |   |
|-----------|---|
| 08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances |
|-----------|---|
- **Uncleaned packaging:**
  - **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |   |  |
|---|--|
| · <b>14.1 UN-Number</b>   | UN2735   |
| · <b>ADR, IMDG, IATA</b>  |  |
| · <b>14.2 UN proper shipping name</b>   | 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)) |
| · <b>ADR</b>  |  |
| · <b>IMDG, IATA</b>   | AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))      |
| · <b>14.3 Transport hazard class(es)</b>  |  |
| · <b>ADR, IMDG, IATA</b>  |  |
|  |  |
| · <b>Class</b>  | 8 Corrosive substances.  |

(Contd. on page 7)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.08.2016

Revision: 08.08.2016

Trade name: Robust™ Epoxy - Primer &amp; Lim, Komp. B

(Contd. of page 6)

· <b>Label</b>	8
· <b>14.4 Packing group</b> · <b>ADR, IMDG, IATA</b>	III
· <b>14.5 Environmental hazards:</b> · <b>Marine pollutant:</b>	No
· <b>14.6 Special precautions for user</b> · <b>Danger code (Kemler):</b> · <b>EMS Number:</b> · <b>Segregation groups</b>	Warning: Corrosive substances. 80 F-A,S-B Alkalis
· <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>ADR</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>Transport category</b> · <b>Tunnel restriction code</b>	3 E
· <b>IMDG</b> · <b>Limited quantities (LQ)</b> · <b>Excepted quantities (EQ)</b>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN2735, AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)), 8, III

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3
- **National regulations:**
- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **Other regulations, limitations and prohibitive regulations**  
For activities involving exposure to uncured epoxy resins and contact via the skin or the respiratory tract regular checkups are causing.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H332 Harmful if inhaled.  
H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 08.08.2016

Revision: 08.08.2016

**Trade name: Robust™ Epoxy - Primer & Lim, Komp. B**

(Contd. of page 7)

**· Abbreviations and acronyms:**

*RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*

*IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)*

*ICAO: International Civil Aviation Organisation*

*ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)*

*ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*IATA: International Air Transport Association*

*GHS: Globally Harmonised System of Classification and Labelling of Chemicals*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*Acute Tox. 4: Acute toxicity – Category 4*

*Skin Corr. 1B: Skin corrosion/irritation – Category 1B*

*Eye Dam. 1: Serious eye damage/eye irritation – Category 1*

*Skin Sens. 1: Skin sensitisation – Category 1*

*Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

GB