

Printing date 08.08.2016 Revision: 08.08.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: RobustTM Epoxy Primer&Maling, Komp. B
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Solvent-free, 2-component, waterborne epoxy paint for floor and wall surfaces, inside and out.

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Steinhardt AS

Postboks 8627 Ranheim

7052 Trondheim

Norway

· Further information obtainable from:

Steinhardt AS

Postboks 8627 Ranheim

7052 Trondheim

+47 72607060. www.robustnorge.no

· 1.4 Emergency telephone number:

(+47) 22591300

https://helsenorge.no/Giftinformasjon

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS07

GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700) phenol, polymer with formaldehyde, glycidyl ether oxirane, mono[(C12-14-alkyloxy)methyl] derivs

(Contd. on page 2)

Printing date 08.08.2016 Revision: 08.08.2016

Trade name: Robust™ Epoxy Primer&Maling, Komp. B

(Contd. of page 1)

· Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P262 Do not get in eyes, on skin, or on clothing.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P360 Rinse immediately contaminated clothing and skin with plenty of water before removing clothes.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- \cdot **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions

· Dangerous components:			
	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700)	>50-<75%	
	Aquatic Chronic 2, H411; 🔷 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317		
CAS: 68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs	>1-<20%	
EINECS: 271-846-8	💠 Skin Irrit. 2, H315; Skin Sens. 1, H317		
CAS: 28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	>10-<20%	
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317		

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

GISCODE: $RE\ 1\ (Part\ A+B)$.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

GB ·

Printing date 08.08.2016 Revision: 08.08.2016

Trade name: Robust™ Epoxy Primer&Maling, Komp. B

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · For safety reasons unsuitable extinguishing agents: Water jet.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: In case of fire use breathing apparatus with independent air supply.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep people away. Ensure adequate ventilation.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter into drains / surface waters / groundwater.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Keep in the original container.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: Store in a cool, dry place.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: VCI: 10
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- · Respiratory protection: With good ventilation: not required.
- · Protection of hands:

Protective gloves

(Contd. on page 4)

Printing date 08.08.2016 Revision: 08.08.2016

Trade name: Robust™ Epoxy Primer&Maling, Komp. B

(Contd. of page 3)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Gloves of nitrile or butyl rubber.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Tightly sealed goggles

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: transparent
Odour: Characteristic

- · pH-value: n.a.
- · Change in condition

Melting point/Melting range: Undetermined. **Boiling point/Boiling range:** > 200 °C

- · Flash point: 140 °C · Ignition temperature: 450 °C
- · Self-igniting: Product is not selfigniting.
- Danger of explosion: Product does not present an explosion hazard.
- · Vapour pressure at 50 °C: <5 hPa
- Density at 20 °C: 1.12 g/cm^3
- · Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Viscosity:

Dynamic at 20 °C: 1000 mPas

• 9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials:

Keep away from strongly acidic and alkaline materials and oxidizing agents to avoid exothermic reactions.

(Contd. on page 5)

Printing date 08.08.2016 Revision: 08.08.2016

Trade name: Robust™ Epoxy Primer&Maling, Komp. B

(Contd. of page 4)

· 10.6 Hazardous decomposition products:

At high temperatures may produce carbon dioxide, carbon monoxide, smoke and nitrogen oxides.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN-Number
- · ADR, IMDG, IATA UN3082

(Contd. on page 6)

Printing date 08.08.2016 Revision: 08.08.2016

 $\textit{Trade name: Robust}^{\text{\tiny{TM}}} \; \textit{Epoxy Primer\&Maling, Komp. B}$

	(Contd. of page	
· 14.2 UN proper shipping name		
· ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number average molecula weight = 700), Bisphenol-F Epichlorhydrinhai Reaktionspr. Phenol-Formaldehyd Novolak m Epichlorhydrin)	
· IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number average molecula weight = 700), Bisphenol-F Epichlorhydrinhan Reaktionspr. Phenol-Formaldehyd Novolak m Epichlorhydrin), MARINE POLLUTANT	
· IATA	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (reaction product: bisphenol-A (epichlorhydrin) epoxy resin (number average molecula weight = 700), Bisphenol-F Epichlorhydrinhan Reaktionspr. Phenol-Formaldehyd Novolak m Epichlorhydrin)	
· 14.3 Transport hazard class(es)		
· ADR, IMDG, IATA		
· Class · Label	9 Miscellaneous dangerous substances and articles. 9	
· 14.4 Packing group · ADR	III	
	III	
· 14.5 Environmental hazards:	Symbol (fish and tree)	
· Marine pollutant: · Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)	
· Special marking (IATA):	Symbol (fish and tree)	
· 14.6 Special precautions for user · Danger code (Kemler):	Warning: Miscellaneous dangerous substances an articles. 90	
· 14.7 Transport in bulk according to Anno Marpol and the IBC Code	ex II of Not applicable.	
$\cdot \textit{Transport/Additional information:}$		
· ADR		
· Limited quantities (LQ)	5L	
· Transport category	3	
· Tunnel restriction code	E	
· UN "Model Regulation":	UN3082, ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (reaction produc bisphenol-A-(epichlorhydrin) epoxy resin (number averag molecular weight = 700), Bisphenol-F Epichlorhydrinha Reaktionspr. Phenol-Formaldehyd Novolak m Epichlorhydrin), 9, III	

Printing date 08.08.2016 Revision: 08.08.2016

Trade name: Robust™ Epoxy Primer&Maling, Komp. B

(Contd. of page 6)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · National regulations:
- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · Other regulations, limitations and prohibitive regulations

This product is subject to Directive 2004/42 / EC.

EU limit value for this product is used in the finished state: 140 g / l (2007); 140 g / l (2010).

The product contains in-hand finished state: <5 g / l VOC.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

PBT: Persistent, Bioaccumulative and Toxic

 $vPvB: very\ Persistent\ and\ very\ Bioaccumulative$

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

- GB