

# Declaration of performance

According to (EU) Nr. 305/2011

## Robust Våtromssystem

DoP Robust Våtromsmembran-02

1. Unique identification code of product type **ETAG 022-1**.
2. Type-, batch- or serial number or any other element allowing identification of the construction product as required under Article 11 (4). **Batch number: see packaging label.**
3. Use intended by the manufacturer or intended use of the construction product according to the applicable harmonised technical specification: **Liquid Applied Coverings with Wearing Surface.**
4. Name, registered trade name or registered trademark and contact address of the manufacturer according Article 11(5): **Steinhardt AS. Pir 2, nr. 10. NO-7010 Trondheim.**
5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2): **not relevant.**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex 5. **System 2+**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: **not relevant.**
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **Notified Body Säurefliesner Vereinigung e.V. (code number 1212) performed the initial inspection of the manufacturing plant and of factory production control (FPC) and the continuous surveillance, assessment, and evaluation of FPC and issued the certificate of conformity of the FPC no. 1212-CPR-2102.**

9. Declared performance

Essential characteristics	Performance	European Technical Approval Guideline
Crack bridging ability	Class 1: 0,4 mm	ETAG 022-1
Bond strength	Class 2: 0,5 Mpa.	ETAG 022-1
Joint bridging ability	Class 2: watertight	ETAG 022-1
Watertightness around penetrations	Class 2: watertight	ETAG 022-1
Resistance to temperature	Class 2: 0,5 Mpa.	ETAG 022-1
Resistance to water	Class 2: 0,5 Mpa.	ETAG 022-1
Resistance to alkalinity	Class 2: 0,5 Mpa.	ETAG 022-1

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

**Stian Schevig**  
Manager/Owner  
Steinhardt AS