

# Product data sheet

<b>Product</b>	<b>Robust™ Rørmansjett</b>
<b>Description</b>	<p>Elastic both sided fleece coated packing for a permanent sealing of pipe passages in combination with Robust Våtromsmembran under tiles. Robust Rørmansjett (8-28mm, 25-60mm og 72-110mm) is watertight, permanently elastic sealing. The packing is made from fleece coated rubber with a central flexible zone. This material basis causes an excellent bonding with almost any waterproofing materials used under tiles extending over the entire surface of the packing.</p> <ul style="list-style-type: none"><li>• Easy to use with premade hole</li><li>• Elastic</li><li>• ETAG 022 approved</li><li>• To be used with Robust Våtrommembran</li></ul>
<b>Preparation</b>	<p>All loose material, soft or crumbling plaster, dirt and poorly bonded layers of paint must be removed. Absorbent surfaces should be primed with Robust™ Primer - Sugende.</p>
<b>Application</b>	<p>Robust Rørmansjett is suitable as permanently watertight sealing on wall/floor areas for pipe passages of shower and bathtub water fittings under ceramic coverings. The packing is complete embedded into the sealing compound. The packing is put over the pipe passage, laid and pressed into the fresh sealing mass. When applying the second coating with the sealing mass the entire packing is coated as well. When the waterproofing system has to be applied in one coat the packing is laid into a previously applied thin layer of the system before the system is applied over the whole area.</p>
<b>Further processing</b>	<p>Robust Rørmansjett is absolutely siliconecompatible; a soaking must not be expected. For lining the joints usual silicones may be applied. Solvent-free adhesives and coatings may be applied directly onto the Robust Rørmansjett packing. Before applying further products a compatibility test has to be carried out.</p>
<b>Finishing</b>	<p>Tools and soiled areas should be cleaned immediately after use with water.</p>
<b>Storage</b>	<p>Robust Rørmansjett can be used for a period of at least 24 months when stored in a cool and dry period.</p>
<b>Technical data</b>	<p><b>Measurements:</b> 100 and 200mm squared.</p> <p><b>Thickness:</b> 0.6 mm.</p>

**Temperature resistance:** -20°C to +90°C.

---

**Colour:** Grey or Blue.

---

**Safety**

The product is not hazardous as defined in the hazardous substances code. May be disposed of as building site waste. For health, safety and environment information please read the safety data sheet at [www.robustnorge.no](http://www.robustnorge.no).

---

**Packaging**

20 pieces per carton.

---

**GTIN**

**8-28mm: GTIN:** 7090040902429  
**25-60mm: GTIN:** 7090040902443  
**72-110mm: GTIN:** 7090040902467

---

**Item no**

**8-28mm. Vare nr.:** 242  
**25-60mm. Vare nr.:** 244  
**72-110mm. Vare nr.:** 246

---

**Nobb**

---

**Warning**

All details in this technical information are based on our current knowledge and experience. They are non-binding and do not release the buyer from the duty to undertake their own tests for suitability for the intended application and purpose. A guarantee for the general validity of all details is ruled out with regard to the different processing and construction site conditions. The general rules for construction engineering as well as the valid standards and guidelines must be observed. The publication of this technical information replaces all previous editions. Changes in the scope of product and application engineering further development are reserved. Please obtain the latest information from our internet sites, [www.robustnorge.no](http://www.robustnorge.no).

---

**Date of issue**

01.06.2016

---

**Company**

**Steinhardt™ AS**  
Org. no. 915496059 mva  
[contact@steinhardt.no](mailto:contact@steinhardt.no)  
[www.steinhardt.no](http://www.steinhardt.no)

---